



## 50mm & 75mm HIGH JUMBO™ RAMP

- 1 Interlocking**  
Each Section has an integral interlocking facility for ease of siting and installation.
- 2 Reflectors**  
Each inner section has incorporated white reflectors for extra visibility.
- 3 Hose / Cables Channel**  
40mm x 25mm channel on the underside allowing for hose/cables to be located in.
- 4 Pre-Drilled Bolt Holes**  
All sections are pre-drilled ready for inserting relevant bolt for specific road surface, i.e. concrete or asphalt.
- 5 Branding Area**  
120mm x 60mm area allowing for client name to be embossed within.



Made from 100% recycled PVC.




• Available in 250mm and 500mm lengths

Product Specifications per pair of Jumbo™ Ramps				
Jumbo 250 Inners (x2):	H=50mm	L=500mm (250mm x 2)	x W=400mm	8.2kg
	H=75mm	L=500mm (250mm x 2)	x W=400mm	16kg
Jumbo 500 Inners (x2):	H=50mm	L=1000mm (500mm x 2)	x W=400mm	16kg
	H=75mm	L=1000mm (500mm x 2)	x W=400mm	22kg
Jumbo End Caps (x2):	H=50mm	L=400mm (200mm x 2)	x W=400mm	4.5kg
	H=75mm	L=400mm (200mm x 2)	x W=400mm	9kg

### Applications for Jumbo™ Ramps

- **50mm high** Jumbo ramps are designed to prevent incidents in and around the workplace, reducing speed to a maximum of 10mph, ideal for reception car-parks, schools, colleges, hospitals etc
- **75mm high** Jumbo ramps are aimed to reduce speed to a maximum of 4mph, ideal for dock-yards, loading bays, bus depots etc



50mm High



75mm High